

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/15/2016

Revision date: 01/11/2022

Supersedes: 12/10/2019

Version: 1.5

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : P-80 QUICK DRYING METAL PRIMER- 1753 GRAY  
 Product code : 731750

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Rodda Paint Co.  
 6107 North Marine Drive  
 Portland, Oregon 97203 - US  
 T (503) 521-4300  
[www.rodmapaint.com](http://www.rodmapaint.com)

#### 1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids Category 3	H226	Flammable liquid and vapour
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 1B	H340	May cause genetic defects
Carcinogenicity Category 1A	H350	May cause cancer
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 1	H400	Very toxic to aquatic life

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapour  
 H317 - May cause an allergic skin reaction  
 H340 - May cause genetic defects  
 H350 - May cause cancer  
 H373 - May cause damage to organs through prolonged or repeated exposure  
 H400 - Very toxic to aquatic life

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.  
 P233 - Keep container tightly closed.  
 P240 - Ground/Bond container and receiving equipment  
 P241 - Use explosion-proof electrical, lighting, ventilating equipment  
 P242 - Use only non-sparking tools.  
 P260 - Do not breathe mist, spray, vapors.

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash hands, forearms and face, clothing, Skin thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P273 - Avoid release to the environment.  
P280 - Wear eye protection, face protection, protective clothing, protective gloves.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P314 - Get medical advice/attention if you feel unwell.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use ABC-powder, dry sand, foam to extinguish.  
P391 - Collect spillage.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	21.4 - 21.7	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Aquatic Acute 1, H400
VM&P NAPTHA	(CAS-No.) 64742-89-8	20.4	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
TITANIUM DIOXIDE	(CAS-No.) 13463-67-7	4.9	Carc. 2, H351
ETHYLBENZENE	(CAS-No.) 100-41-4	4.7 - 4.8	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
ISOPROPANOL	(CAS-No.) 67-63-0	1	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 STOT SE 3, H336
MINERAL SPIRITS	(CAS-No.) 64741-65-7	0.3	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401
METHYL ETHYL KETOXIME	(CAS-No.) 96-29-7	0.2	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
CARBON BLACK	(CAS-No.) 1333-86-4	0.1	Carc. 2, H351
QUARTZ	(CAS-No.) 14808-60-7	0.1	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
-------------------------------------	--

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour.
Reactivity	: Flammable liquid and vapour.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures	: NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe mist, vapors, spray.
----------------------	--

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8 "Exposure controls/personal protection".
----------------------	--

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist, vapors, spray. Avoid contact with skin and eyes.
-------------------------------	---

Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
------------------	---

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
--------------------	--

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>MINERAL SPIRITS (64741-65-7)</b>		
Not applicable		
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) [1]	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
<b>ETHYLBENZENE (100-41-4)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) [1]	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
<b>METHYL ETHYL KETOXIME (96-29-7)</b>		
AIHA	WEEL TWA (ppm)	10 ppm
<b>QUARTZ (14808-60-7)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
OSHA	OSHA PEL (TWA) [1]	50 µg/m <sup>3</sup>
IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
<b>ISOPROPANOL (67-63-0)</b>		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	400 ppm
OSHA	OSHA PEL (TWA) [1]	980 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
<b>VM&amp;P NAPHTHA (64742-89-8)</b>		
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
<b>TITANIUM DIOXIDE (13463-67-7)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) [1]	15 mg/m <sup>3</sup> (total dust)
IDLH	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TITANIUM DIOXIDE (13463-67-7)		
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2.4 mg/m <sup>3</sup> (CIB 63-fine) 0.3 mg/m <sup>3</sup> (CIB 63-ultrafine, including engineered nanoscale)
CARBON BLACK (1333-86-4)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable particulate matter)
OSHA	OSHA PEL (TWA) [1]	3.5 mg/m <sup>3</sup>
IDLH	US IDLH (mg/m <sup>3</sup> )	1750 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> (Carbon black in presence of Polycyclic aromatic hydrocarbons)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: grey
Odor	: aromatic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 44 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity	: No data available

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific gravity / density	: 9.37 lb/gal
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 300 cSt
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon dioxide. Carbon monoxide. fume.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>MINERAL SPIRITS (64741-65-7)</b>	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h
ATE US (vapors)	3 mg/l/4h
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat (mg/l)	29.08 mg/l/4h
ATE US (oral)	3500 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>ETHYLBENZENE (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.4 mg/l/4h
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15400 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.4 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	1000 - 1800 mg/kg
LC50 inhalation rat (mg/l)	> 4800 mg/l (Exposure time: 4 h)
ATE US (oral)	930 mg/kg body weight
ATE US (dermal)	1000 mg/kg body weight

<b>ISOPROPANOL (67-63-0)</b>	
LD50 oral rat	1870 mg/kg
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat (mg/l)	72600 mg/m <sup>3</sup> (Exposure time: 4 h)
ATE US (oral)	1870 mg/kg body weight
ATE US (dermal)	4059 mg/kg body weight

<b>VM&amp;P NAPHTHA (64742-89-8)</b>	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h
ATE US (dermal)	3000 mg/kg body weight
ATE US (gases)	3400 ppmV/4h

<b>TITANIUM DIOXIDE (13463-67-7)</b>	
LD50 oral rat	> 10000 mg/kg

<b>CARBON BLACK (1333-86-4)</b>	
LD50 oral rat	> 15400 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3 - Not Classifiable

<b>ETHYLBENZENE (100-41-4)</b>	
IARC group	2B - Possibly Carcinogenic to Humans
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

<b>QUARTZ (14808-60-7)</b>	
IARC group	1 - Carcinogenic to Humans
National Toxicity Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

<b>ISOPROPANOL (67-63-0)</b>	
IARC group	3 - Not Classifiable

<b>TITANIUM DIOXIDE (13463-67-7)</b>	
IARC group	2B - Possibly Carcinogenic to Humans
In OSHA Hazard Communication Carcinogen list	Yes

<b>CARBON BLACK (1333-86-4)</b>	
IARC group	2B - Possibly Carcinogenic to Humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Very toxic to aquatic life.

<b>MINERAL SPIRITS (64741-65-7)</b>	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
<b>ETHYLBENZENE (100-41-4)</b>	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
<b>ISOPROPANOL (67-63-0)</b>	
LC50 fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15
<b>ETHYLBENZENE (100-41-4)</b>	
BCF fish 1	15
Log Pow	3.2
<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)
<b>ISOPROPANOL (67-63-0)</b>	
Log Pow	0.05 (at 25 °C)

#### 12.4. Mobility in soil

No additional information available



# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose of contents/container to hazardous or special waste collection point in accordance with state and local regulations.
- Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1263 Paint, 3, III
- UN-No.(DOT) : UN1263
- Proper Shipping Name (DOT) : Paint
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Packing group (DOT) : III - Minor Danger
- Hazard labels (DOT) : 3 - Flammable liquid



- Dangerous for the environment : Yes
- Marine pollutant : Yes



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
- DOT Packaging Bulk (49 CFR 173.xxx) : 242

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

### Transportation of Dangerous Goods

Not applicable

### Transport by sea

Transport document description (IMDG)	: UN 1263 PAINT, 3, III
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L
Marine pollutant	: Yes



### Air transport

Transport document description (IATA)	: UN 1263 Paint, 3, III
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IATA)

: III - Minor Danger

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Xylenes (o-, m-, p- isomers)	CAS-No. 1330-20-7	21.4 - 21.7%
ETHYLBENZENE	CAS-No. 100-41-4	4.7 - 4.8%
ISOPROPANOL	CAS-No. 67-63-0	1%

#### MINERAL SPIRITS (64741-65-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 100 lb

#### ETHYLBENZENE (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

CERCLA RQ 1000 lb

#### METHYL ETHYL KETOXIME (96-29-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### QUARTZ (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### ISOPROPANOL (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### VM&P NAPHTHA (64742-89-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### TITANIUM DIOXIDE (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### CARBON BLACK (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

#### MINERAL SPIRITS (64741-65-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### ETHYLBENZENE (100-41-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### METHYL ETHYL KETOXIME (96-29-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Toxic Substance (CEPA – Schedule I) Yes

#### QUARTZ (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### ISOPROPANOL (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### VM&P NAPHTHA (64742-89-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### TITANIUM DIOXIDE (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

### CARBON BLACK (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

### EU-Regulations

#### MINERAL SPIRITS (64741-65-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### ETHYLBENZENE (100-41-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### METHYL ETHYL KETOXIME (96-29-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### QUARTZ (14808-60-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### ISOPROPANOL (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### VM&P NAPHTHA (64742-89-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### TITANIUM DIOXIDE (13463-67-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### CARBON BLACK (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

Listed on European List of Notified Chemical Substances (ELINCS)

### National regulations

#### MINERAL SPIRITS (64741-65-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on Industrial Safety and Health Law Substances (ISHL)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Poisonous and Deleterious Substances Control Law  
Pollutant Release and Transfer Register Law (PRTR Law)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on EPA Hazardous Air Pollutant (HAPS)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

#### ETHYLBENZENE (100-41-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on Industrial Safety and Health Law Substances (ISHL)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Pollutant Release and Transfer Register Law (PRTR Law)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on EPA Hazardous Air Pollutant (HAPS)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### METHYL ETHYL KETOXIME (96-29-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on Industrial Safety and Health Law Substances (ISHL)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### QUARTZ (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on Industrial Safety and Health Law Substances (ISHL)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### ISOPROPANOL (67-63-0)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on Industrial Safety and Health Law Substances (ISHL)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### VM&P NAPHTHA (64742-89-8)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)


### TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on Industrial Safety and Health Law Substances (ISHL)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### CARBON BLACK (1333-86-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on Industrial Safety and Health Law Substances (ISHL)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### 15.3. US State regulations

 **WARNING** This product can expose you to ETHYLBENZENE, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLBENZENE (100-41-4)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	54 µg/day	

TITANIUM DIOXIDE (13463-67-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

CARBON BLACK (1333-86-4)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Xylenes (o-, m-, p- isomers) (1330-20-7)					
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List					

ETHYLBENZENE (100-41-4)					
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List					

QUARTZ (14808-60-7)					
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List					

ISOPROPANOL (67-63-0)					
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List					

TITANIUM DIOXIDE (13463-67-7)					
U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List					

# P-80 QUICK DRYING METAL PRIMER- 1753 GRAY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### CARBON BLACK (1333-86-4)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances  
U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Revision date : 01/11/2022

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life

SDS US (GHS HazCom 2012)

*RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.*