



FINISH RIGHT

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/24/2016

Revision date: 01/21/2017

Supersedes: 02/24/2016

Version: 1.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : PORSALITE LOW GLOSS ENAMEL - WHITE  
 Product code : 735001

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Rodda Paint Co.  
 6107 North Marine Drive  
 Portland, Oregon 97203 - US  
 T (503) 521-4300  
[www.rodmapaint.com](http://www.rodmapaint.com)

#### 1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids H226  
 Category 3  
 Skin sensitization H317  
 Category 1  
 Germ cell mutagenicity H340  
 Category 1B  
 Carcinogenicity H350  
 Category 1A  
 Hazardous to the H401  
 aquatic environment -  
 Acute Hazard Category  
 2

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
 H317 - May cause an allergic skin reaction  
 H340 - May cause genetic defects  
 H350 - May cause cancer  
 H401 - Toxic to aquatic life

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
 P233 - Keep container tightly closed  
 P240 - Ground/Bond container and receiving equipment  
 P241 - Use explosion-proof electrical, lighting, ventilating equipment  
 P242 - Use only non-sparking tools  
 P243 - Take precautionary measures against static discharge  
 P261 - Avoid breathing fume, spray, vapors  
 P272 - Contaminated work clothing must not be allowed out of the workplace  
 P273 - Avoid release to the environment  
 P280 - Wear eye protection, protective clothing, protective gloves

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P321 - Specific treatment (see In all cases of doubt, or when symptoms persist, seek medical attention on this label)  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), ABC-powder, foam to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
MINERAL SPIRITS	(CAS No) 64741-65-7	25.7	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
TITANIUM DIOXIDE	(CAS No) 13463-67-7	18.4	Carc. 2, H351
TALC substance with OEL values	(CAS No) 14807-96-6	14.9	Not classified
CALCIUM CARBONATE substance with OEL values	(CAS No) 1317-65-3	11.3	Not classified
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	(CAS No) 64742-48-9	0.6	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
ETHYLBENZENE	(CAS No) 100-41-4	0.4	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
ETHANOL	(CAS No) 64-17-5	0.3	Flam. Liq. 2, H225 Carc. 1A, H350
METHYL ETHYL KETOXIME	(CAS No) 96-29-7	0.2	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.  
Reactivity : Flammable liquid and vapor.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust, fume.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing dust, fume.  
Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Protect from freezing. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### METHYL ETHYL KETOXIME (96-29-7)

AIHA	WEEL TWA (ppm)	10 ppm
------	----------------	--------

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>TALC (14807-96-6)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
IDLH	US IDLH (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup> (containing no asbestos and <1% quartz)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (containing no Asbestos and <1% Quartz-respirable dust)
<b>MINERAL SPIRITS (64741-65-7)</b>		
Not applicable		
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)</b>		
Not applicable		
<b>ETHYLBENZENE (100-41-4)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
<b>ETHANOL (64-17-5)</b>		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
<b>CALCIUM CARBONATE (1317-65-3)</b>		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>TITANIUM DIOXIDE (13463-67-7)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
IDLH	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>

### 8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Personal protective equipment

: Gloves. Safety glasses. Protective clothing. Dust/aerosol mask.



Hand protection

: Protective gloves.

Eye protection

: Safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Wear respiratory protection.

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls : Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : white  
Odor : aromatic  
Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 40 °C  
Relative evaporation rate (butyl acetate=1) : Faster than butyl acetate  
Flammability (solid, gas) : Not applicable.  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Specific gravity : No data available  
Specific gravity / density : 11.08 lb/gal  
Solubility : No data available  
Log Pow : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity, kinematic : ≈ 760 cSt  
Viscosity, dynamic : No data available  
Explosion limits : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapor.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Carbon dioxide. Carbon monoxide. fume.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### METHYL ETHYL KETOXIME (96-29-7)

LD50 oral rat	930 mg/kg
---------------	-----------

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
LD50 dermal rabbit	1000 - 1800 mg/kg
LC50 inhalation rat (mg/l)	> 4800 mg/l (Exposure time: 4 h)
ATE US (oral)	930.000 mg/kg body weight
ATE US (dermal)	1000.000 mg/kg body weight

<b>MINERAL SPIRITS (64741-65-7)</b>	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h

<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg

<b>ETHYLBENZENE (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.4 mg/l/4h
ATE US (oral)	3500.000 mg/kg body weight
ATE US (dermal)	15400.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	17.400 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

<b>ETHANOL (64-17-5)</b>	
LD50 oral rat	7060 mg/kg
LC50 inhalation rat (mg/l)	124.7 mg/l/4h
ATE US (oral)	7060.000 mg/kg body weight
ATE US (vapors)	124.700 mg/l/4h
ATE US (dust, mist)	124.700 mg/l/4h

<b>TITANIUM DIOXIDE (13463-67-7)</b>	
LD50 oral rat	> 10000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

<b>TALC (14807-96-6)</b>	
IARC group	3 - Not Classifiable
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

<b>ETHYLBENZENE (100-41-4)</b>	
IARC group	2B - Possibly Carcinogenic to Humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

<b>ETHANOL (64-17-5)</b>	
IARC group	1 - Carcinogenic to Humans
In OSHA Hazard Communication Carcinogen list	Yes

<b>TITANIUM DIOXIDE (13463-67-7)</b>	
IARC group	2B - Possibly Carcinogenic to Humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Toxic to aquatic life.

<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
<b>TALC (14807-96-6)</b>	
LC50 fish 1	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
<b>MINERAL SPIRITS (64741-65-7)</b>	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)</b>	
LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
<b>ETHYLBENZENE (100-41-4)</b>	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
<b>ETHANOL (64-17-5)</b>	
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)
<b>TALC (14807-96-6)</b>	
BCF fish 1	(no known bioaccumulation)
<b>ETHYLBENZENE (100-41-4)</b>	
BCF fish 1	15
Log Pow	3.2
<b>ETHANOL (64-17-5)</b>	
Log Pow	-0.32

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Effect on the global warming : No known effects from this product.  
GWPmix comment : No known effects from this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Waste disposal recommendations : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose of contents/container to hazardous or special waste collection point in accordance with state and local regulations.  
Additional information : Flammable vapors may accumulate in the container.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : ID8000 Consumer commodity, 9  
UN-No.(DOT) : ID8000  
Proper Shipping Name (DOT) : Consumer commodity  
Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140  
Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



DOT Packaging Non Bulk (49 CFR 173.xxx) : 167  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Packaging Exceptions (49 CFR 173.xxx) : 167  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 30 kg gross  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 kg gross  
Emergency Response Guide (ERG) Number : 171  
Other information : No supplementary information available.

#### TDG

#### Transport by sea

Not regulated

#### Air transport

Not regulated

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ETHYLBENZENE	CAS No 100-41-4	0.4%
--------------	-----------------	------

#### METHYL ETHYL KETOXIME (96-29-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### TALC (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory



# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>MINERAL SPIRITS (64741-65-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>ETHYLBENZENE (100-41-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
<b>ETHANOL (64-17-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>CALCIUM CARBONATE (1317-65-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>TITANIUM DIOXIDE (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. International regulations

#### CANADA

<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory	
<b>TALC (14807-96-6)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>MINERAL SPIRITS (64741-65-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory	
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 3 - Combustible Liquid
<b>ETHYLBENZENE (100-41-4)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>ETHANOL (64-17-5)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>CALCIUM CARBONATE (1317-65-3)</b>	
Listed on Non-Domestic Substances List (NDSL)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>TITANIUM DIOXIDE (13463-67-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

#### EU-Regulations

<b>METHYL ETHYL KETOXIME (96-29-7)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
<b>TALC (14807-96-6)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
<b>MINERAL SPIRITS (64741-65-7)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

### **ETHYLBENZENE (100-41-4)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

### **ETHANOL (64-17-5)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

### **CALCIUM CARBONATE (1317-65-3)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

### **TITANIUM DIOXIDE (13463-67-7)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

## National regulations

### **METHYL ETHYL KETOXIME (96-29-7)**

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

### **TALC (14807-96-6)**

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

### **MINERAL SPIRITS (64741-65-7)**

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

### **NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)**

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

### **ETHYLBENZENE (100-41-4)**

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Pollutant Release and Transfer Register Law (PRTR Law)  
Listed on the Canadian Ingredient Disclosure List  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### ETHANOL (64-17-5)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on the Canadian Ingredient Disclosure List  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

### CALCIUM CARBONATE (1317-65-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

### TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory  
Listed on the Korean ECL (Existing Chemical List) inventory  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

### ETHYLBENZENE (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	54 µg/day

### ETHANOL (64-17-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	

### TITANIUM DIOXIDE (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

### TALC (14807-96-6)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### ETHYLBENZENE (100-41-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

# PORSALITE LOW GLOSS ENAMEL - WHITE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### ETHANOL (64-17-5)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### CALCIUM CARBONATE (1317-65-3)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### TITANIUM DIOXIDE (13463-67-7)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Revision date : 01/21/2017

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life

SDS US (GHS HazCom 2012)

*RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.*