



FINISH RIGHT

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/22/2016

Revision date: 04/24/2020

Supersedes: 01/22/2016

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : SPEED PRIMER WHITE
 Product code : 702901

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Solventborne Coating

1.3. Supplier

Rodda Paint Co.
 6107 North Marine Drive
 Portland, Oregon 97203 - US
 T (503) 521-4300
www.rodmapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids, Category 2	H225	Highly flammable liquid and vapour.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Germ cell mutagenicity, Category 1B	H340	May cause genetic defects.
Carcinogenicity, Category 1A	H350	May cause cancer.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour.
 H317 - May cause an allergic skin reaction.
 H340 - May cause genetic defects.
 H350 - May cause cancer.
 H373 - May cause damage to organs through prolonged or repeated exposure.
 H402 - Harmful to aquatic life

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, open flames, sparks. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment
 P241 - Use explosion-proof electrical, lighting, ventilating equipment.
 P242 - Use only non-sparking tools.
 P260 - Do not breathe vapours, mist, fume.
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P273 - Avoid release to the environment.

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves, eye protection, protective clothing.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P314 - Get medical advice/attention if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use ABC-powder, carbon dioxide (CO₂), foam to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
TITANIUM DIOXIDE	(CAS-No.) 13463-67-7	14.3	Carc. 2, H351
VM&P NAPHTHA	(CAS-No.) 64742-89-8	11.4	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	9.7 - 10.1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Aquatic Acute 1, H400
MINERAL SPIRITS	(CAS-No.) 64741-65-7	6.5	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401
ETHYLBENZENE	(CAS-No.) 100-41-4	1.9 - 2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
SOLVENT NAPHTHA, LIGHT AROMATIC	(CAS-No.) 64742-95-6	2	Flam. Liq. 1, H224 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 2, H401
SILICA-CRYSTALLINE	(CAS-No.) 14464-46-1	1.5	Carc. 1A, H350
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	(CAS-No.) 64742-48-9	0.3	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
METHYL ETHYL KETOXIME	(CAS-No.) 96-29-7	0.2	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
QUARTZ	(CAS-No.) 14808-60-7	0.1	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
-------------------------------------	--

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Reactivity	: Highly flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe mist, vapours, spray.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist, vapours, spray. Avoid contact with skin and eyes.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VM&P NAPHTHA (64742-89-8)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³
MINERAL SPIRITS (64741-65-7)		
Not applicable		
ETHYLBENZENE (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)		
Not applicable		
TITANIUM DIOXIDE (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
IDLH	US IDLH (mg/m ³)	5000 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)
QUARTZ (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
SILICA-CRYSTALLINE (14464-46-1)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
IDLH	US IDLH (mg/m ³)	25 mg/m ³ (respirable dust)
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Not applicable		
Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
METHYL ETHYL KETOXIME (96-29-7)		
AIHA	WEEL TWA (ppm)	10 ppm

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Dust/aerosol mask. Gloves. In case of splash hazard: safety glasses. In case of dust production: protective goggles. Protective clothing.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : white
Odour : aromatic
Odour threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : 121 - 158 °C
Flash point : > 13 °C
Relative evaporation rate (butylacetate=1) : No data available
Flammability (solid, gas) : Not applicable.
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Specific gravity : No data available
Density : 11 lb/gal
Solubility : No data available
Log Pow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : 300 cSt
Viscosity, dynamic : No data available
Explosive limits : No data available
Explosive properties : No data available
Oxidising properties : No data available

9.2. Other information

No additional information available

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

VM&P NAPHTHA (64742-89-8)	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h
ATE US (dermal)	3000 mg/kg bodyweight
ATE US (gases)	3400 ppmv/4h
MINERAL SPIRITS (64741-65-7)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h
ATE US (vapours)	3 mg/l/4h
ETHYLBENZENE (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.4 mg/l/4h
ATE US (oral)	3500 mg/kg bodyweight
ATE US (dermal)	15400 mg/kg bodyweight
ATE US (gases)	4500 ppmv/4h
ATE US (vapours)	17.4 mg/l/4h
ATE US (dust,mist)	1.5 mg/l/4h
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h
ATE US (oral)	8400 mg/kg bodyweight
ATE US (gases)	3400 ppmv/4h
TITANIUM DIOXIDE (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LD50 oral rat	> 6000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	> 8500 mg/m ³ (Exposure time: 4 h)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 inhalation rat (mg/l)	29.08 mg/l/4h
ATE US (oral)	3500 mg/kg bodyweight
ATE US (gases)	4500 ppmv/4h
ATE US (vapours)	11 mg/l/4h
ATE US (dust,mist)	1.5 mg/l/4h

METHYL ETHYL KETOXIME (96-29-7)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	1000 - 1800 mg/kg
LC50 inhalation rat (mg/l)	> 4800 mg/l (Exposure time: 4 h)
ATE US (oral)	930 mg/kg bodyweight
ATE US (dermal)	1000 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

ETHYLBENZENE (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

TITANIUM DIOXIDE (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

QUARTZ (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

SILICA-CRYSTALLINE (14464-46-1)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Symptoms/effects after skin contact : May cause an allergic skin reaction.

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

MINERAL SPIRITS (64741-65-7)	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)

ETHYLBENZENE (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
LC50 fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

METHYL ETHYL KETOXIME (96-29-7)	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

ETHYLBENZENE (100-41-4)	
BCF fish 1	15
Log Pow	3.2

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15

METHYL ETHYL KETOXIME (96-29-7)	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose of contents/container to hazardous or special waste collection point in accordance with state and local regulations.
- Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, II
- UN-No.(DOT) : UN1263
- Proper Shipping Name (DOT) : Paint related material including paint thinning, drying, removing, or reducing compound
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Packing group (DOT) : II - Medium Danger
- Hazard labels (DOT) : 3 - Flammable liquid



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- Other information : No supplementary information available.

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transportation of Dangerous Goods

Transport by sea

Transport document description (IMDG)	: UN 1263 PAINT RELATED MATERIAL, 3, II
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT RELATED MATERIAL
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 5 L

Air transport

Transport document description (IATA)	: UN 1263 Paint, 3, II
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ETHYLBENZENE	CAS-No. 100-41-4	1.9 - 2%
Xylenes (o-, m-, p- isomers)	CAS-No. 1330-20-7	9.7 - 10.1%

VM&P NAPHTHA (64742-89-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

MINERAL SPIRITS (64741-65-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

ETHYLBENZENE (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
CERCLA RQ	1000 lb

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

TITANIUM DIOXIDE (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

QUARTZ (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SILICA-CRYSTALLINE (14464-46-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

METHYL ETHYL KETOXIME (96-29-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

VM&P NAPHTHA (64742-89-8)	
Listed on the Canadian DSL (Domestic Substances List)	
MINERAL SPIRITS (64741-65-7)	
Listed on the Canadian DSL (Domestic Substances List)	
ETHYLBENZENE (100-41-4)	
Listed on the Canadian DSL (Domestic Substances List)	
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
Listed on the Canadian DSL (Domestic Substances List)	
TITANIUM DIOXIDE (13463-67-7)	
Listed on the Canadian DSL (Domestic Substances List)	
QUARTZ (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
SILICA-CRYSTALLINE (14464-46-1)	
Listed on the Canadian DSL (Domestic Substances List)	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
Listed on the Canadian DSL (Domestic Substances List)	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List)	
METHYL ETHYL KETOXIME (96-29-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Toxic Substance (CEPA – Schedule I)	Yes

EU-Regulations

VM&P NAPHTHA (64742-89-8)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
MINERAL SPIRITS (64741-65-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
ETHYLBENZENE (100-41-4)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
TITANIUM DIOXIDE (13463-67-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
QUARTZ (14808-60-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
SILICA-CRYSTALLINE (14464-46-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
METHYL ETHYL KETOXIME (96-29-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

National regulations

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

VM&P NAPHTHA (64742-89-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

MINERAL SPIRITS (64741-65-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

ETHYLBENZENE (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

QUARTZ (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SILICA-CRYSTALLINE (14464-46-1)

Listed on IARC (International Agency for Research on Cancer)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

METHYL ETHYL KETOXIME (96-29-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

 **WARNING** This product can expose you to ETHYLBENZENE, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

ETHYLBENZENE (100-41-4)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No	54 µg/day	

TITANIUM DIOXIDE (13463-67-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLBENZENE (100-41-4)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

TITANIUM DIOXIDE (13463-67-7)

U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

QUARTZ (14808-60-7)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SILICA-CRYSTALLINE (14464-46-1)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date

: 04/24/2020

SPEED PRIMER WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements:

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life

SDS US (GHS HazCom 2012)

RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.