



RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 07/24/2017 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE
Product code : 714403

1.2. Recommended use and restrictions on use

Recommended use : Coatings and paints

1.3. Supplier

Rodda Paint Co.
6107 North Marine Drive
Portland, Oregon 97203 - US
T (503) 521-4300
www.roddapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | | |
|------------------------------------|------|--|
| Flammable liquids Category 3 | H226 | Flammable liquid and vapor |
| Skin sensitization, Category 1 | H317 | May cause an allergic skin reaction |
| Germ cell mutagenicity Category 1B | H340 | May cause genetic defects (Inhalation, Dermal, oral) |
| Carcinogenicity Category 1A | H350 | May cause cancer (oral, Inhalation, Dermal) |

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02 GHS07 GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor
H317 - May cause an allergic skin reaction
H340 - May cause genetic defects (Inhalation, Dermal, oral)
H350 - May cause cancer (oral, Inhalation, Dermal)

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from sparks, open flames, hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust, mist, fume
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of soap & water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see In all cases of doubt, or when symptoms persist, seek medical attention on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use ABC-powder, carbon dioxide (CO₂), foam, Water fog. to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|---|----------------------|------|---|
| MINERAL SPIRITS | (CAS-No.) 64741-65-7 | 25.5 | Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 |
| TITANIUM DIOXIDE | (CAS-No.) 13463-67-7 | 6.6 | Carc. 2, H351 |
| SILICA-CRYSTALLINE | (CAS-No.) 14464-46-1 | 6.4 | Carc. 1A, H350 |
| ETHYLBENZENE | (CAS-No.) 100-41-4 | 0.3 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 |
| NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | (CAS-No.) 64742-48-9 | 0.3 | Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 |
| QUARTZ | (CAS-No.) 14808-60-7 | 0.2 | Acute Tox. 4 (Oral), H302 Carc. 1A, H350 |
| METHYL ETHYL KETOXIME | (CAS-No.) 96-29-7 | 0.2 | Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Reactivity : Flammable liquid and vapor.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing mist, fume, dust.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing mist, fume, dust.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| TITANIUM DIOXIDE (13463-67-7) | | |
|-------------------------------|-------------------------------------|-----------------------------------|
| ACGIH | ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ (total dust) |
| IDLH | US IDLH (mg/m ³) | 5000 mg/m ³ |
| MINERAL SPIRITS (64741-65-7) | | |
| Not applicable | | |
| ETHYLBENZENE (100-41-4) | | |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| ETHYLBENZENE (100-41-4) | | |
|---|---------------------------------------|---|
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| IDLH | US IDLH (ppm) | 800 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 435 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 545 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 125 ppm |
| QUARTZ (14808-60-7) | | |
| ACGIH | ACGIH TWA (mg/m ³) | 0.025 mg/m ³ (respirable particulate matter) |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 50 µg/m ³ |
| IDLH | US IDLH (mg/m ³) | 50 mg/m ³ (respirable dust) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 0.05 mg/m ³ (respirable dust) |
| NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9) | | |
| Not applicable | | |
| SILICA-CRYSTALLINE (14464-46-1) | | |
| ACGIH | ACGIH TWA (mg/m ³) | 0.025 mg/m ³ (respirable particulate matter) |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 50 µg/m ³ |
| IDLH | US IDLH (mg/m ³) | 25 mg/m ³ (respirable dust) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 0.05 mg/m ³ (respirable dust) |
| METHYL ETHYL KETOXIME (96-29-7) | | |
| AIHA | WEEL TWA (ppm) | 10 ppm |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Dust/aerosol mask. Gloves. Insufficient ventilation: wear respiratory protection. Safety glasses.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection



RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------------------|
| Physical state | : Liquid |
| Appearance | : White liquid before tinting. |
| Color | : white |
| Odor | : mild |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : > 43 °C |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Specific gravity | : 1.29 |
| Specific gravity / density | : 10.71 lb/gal |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

TITANIUM DIOXIDE (13463-67-7)

| | |
|---------------|---------------|
| LD50 oral rat | > 10000 mg/kg |
|---------------|---------------|

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| MINERAL SPIRITS (64741-65-7) | |
|-------------------------------------|----------------|
| LD50 oral rat | > 7000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | > 5.04 mg/l/4h |

| ETHYLBENZENE (100-41-4) | |
|--------------------------------|-----------------------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | 15400 mg/kg |
| LC50 inhalation rat (mg/l) | 17.4 mg/l/4h |
| ATE US (oral) | 3500.000 mg/kg body weight |
| ATE US (dermal) | 15400.000 mg/kg body weight |
| ATE US (gases) | 4500.000 ppmV/4h |
| ATE US (vapors) | 17.400 mg/l/4h |
| ATE US (dust, mist) | 1.500 mg/l/4h |

| QUARTZ (14808-60-7) | |
|----------------------------|---------------------------|
| LD50 oral rat | 500 mg/kg |
| ATE US (oral) | 500.000 mg/kg body weight |

| NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9) | |
|---|---|
| LD50 oral rat | > 6000 mg/kg |
| LD50 dermal rabbit | > 3160 mg/kg |
| LC50 inhalation rat (mg/l) | > 8500 mg/m ³ (Exposure time: 4 h) |

| METHYL ETHYL KETOXIME (96-29-7) | |
|--|----------------------------------|
| LD50 oral rat | 930 mg/kg |
| LD50 dermal rabbit | 1000 - 1800 mg/kg |
| LC50 inhalation rat (mg/l) | > 4800 mg/l (Exposure time: 4 h) |
| ATE US (oral) | 930.000 mg/kg body weight |
| ATE US (dermal) | 1000.000 mg/kg body weight |

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : May cause genetic defects (Inhalation, Dermal, oral).
Carcinogenicity : May cause cancer (oral, Inhalation, Dermal).

| TITANIUM DIOXIDE (13463-67-7) | |
|--|--------------------------------------|
| IARC group | 2B - Possibly Carcinogenic to Humans |
| In OSHA Hazard Communication Carcinogen list | Yes |

| ETHYLBENZENE (100-41-4) | |
|--|--------------------------------------|
| IARC group | 2B - Possibly Carcinogenic to Humans |
| National Toxicity Program (NTP) Status | 1 - Evidence of Carcinogenicity |
| In OSHA Hazard Communication Carcinogen list | Yes |

| QUARTZ (14808-60-7) | |
|--|-----------------------------|
| IARC group | 1 - Carcinogenic to Humans |
| National Toxicity Program (NTP) Status | 2 - Known Human Carcinogens |
| In OSHA Hazard Communication Carcinogen list | Yes |

| SILICA-CRYSTALLINE (14464-46-1) | |
|--|-----------------------------|
| IARC group | 1 - Carcinogenic to Humans |
| National Toxicity Program (NTP) Status | 2 - Known Human Carcinogens |
| In OSHA Hazard Communication Carcinogen list | Yes |

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after skin contact : May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

MINERAL SPIRITS (64741-65-7)

| | |
|----------------|--|
| EC50 Daphnia 1 | 2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia) |
|----------------|--|

ETHYLBENZENE (100-41-4)

| | |
|-------------|--|
| LC50 fish 1 | 11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
|-------------|--|

| | |
|----------------|---|
| EC50 Daphnia 1 | 1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
|----------------|---|

| | |
|-------------|---|
| LC50 fish 2 | 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |
|-------------|---|

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

| | |
|-------------|--|
| LC50 fish 1 | 2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |
|-------------|--|

METHYL ETHYL KETOXIME (96-29-7)

| | |
|-------------|--|
| LC50 fish 1 | 777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
|-------------|--|

| | |
|----------------|---|
| EC50 Daphnia 1 | 750 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
|----------------|---|

| | |
|-------------|--|
| LC50 fish 2 | 760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static]) |
|-------------|--|

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

ETHYLBENZENE (100-41-4)

| | |
|------------|----|
| BCF fish 1 | 15 |
|------------|----|

| | |
|---------|-----|
| Log Pow | 3.2 |
|---------|-----|

METHYL ETHYL KETOXIME (96-29-7)

| | |
|------------|-----------|
| BCF fish 1 | 0.5 - 5.8 |
|------------|-----------|

| | |
|---------|-----------------|
| Log Pow | 0.65 (at 25 °C) |
|---------|-----------------|

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

GWPMix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint, 3, III

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|----------------------------|---|
| UN-No.(DOT) | : UN1263 |
| Proper Shipping Name (DOT) | : Paint |
| Class (DOT) | : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 |
| Packing group (DOT) | : III - Minor Danger |
| Hazard labels (DOT) | : 3 - Flammable liquid |



| | |
|--|--|
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 173 |
| DOT Packaging Bulk (49 CFR 173.xxx) | : 242 |
| DOT Special Provisions (49 CFR 172.102) | : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 150 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 60 L |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 220 L |
| DOT Vessel Stowage Location | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. |
| Emergency Response Guide (ERG) Number | : 128 |
| Other information | : No supplementary information available. |

Transportation of Dangerous Goods

Transport by sea

| | |
|---------------------------------------|--|
| Transport document description (IMDG) | : UN 1263 PAINT, 3, III |
| UN-No. (IMDG) | : 1263 |
| Proper Shipping Name (IMDG) | : PAINT |
| Class (IMDG) | : 3 - Flammable liquids |
| Packing group (IMDG) | : III - substances presenting low danger |
| Limited quantities (IMDG) | : 5 L |

Air transport

| | |
|---------------------------------------|-------------------------|
| Transport document description (IATA) | : UN 1263 Paint, 3, III |
| UN-No. (IATA) | : 1263 |
| Proper Shipping Name (IATA) | : Paint |
| Class (IATA) | : 3 - Flammable Liquids |
| Packing group (IATA) | : III - Minor Danger |

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

| | | |
|---|--|------|
| ETHYLBENZENE | CAS-No. 100-41-4 | 0.3% |
| TITANIUM DIOXIDE (13463-67-7) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| MINERAL SPIRITS (64741-65-7) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| ETHYLBENZENE (100-41-4) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. | |
| CERCLA RQ | 1000 lb | |
| SARA Section 313 - Emission Reporting | 0.1 % | |
| QUARTZ (14808-60-7) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| SILICA-CRYSTALLINE (14464-46-1) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| METHYL ETHYL KETOXIME (96-29-7) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |

15.2. International regulations

CANADA

| | |
|--|--|
| TITANIUM DIOXIDE (13463-67-7) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| MINERAL SPIRITS (64741-65-7) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| ETHYLBENZENE (100-41-4) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| QUARTZ (14808-60-7) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| SILICA-CRYSTALLINE (14464-46-1) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| METHYL ETHYL KETOXIME (96-29-7) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |

EU-Regulations

| | |
|--|--|
| TITANIUM DIOXIDE (13463-67-7) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances. | |
| MINERAL SPIRITS (64741-65-7) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances. | |
| ETHYLBENZENE (100-41-4) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances. | |
| QUARTZ (14808-60-7) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances. | |

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

SILICA-CRYSTALLINE (14464-46-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

METHYL ETHYL KETOXIME (96-29-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

National regulations

TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

MINERAL SPIRITS (64741-65-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

ETHYLBENZENE (100-41-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

QUARTZ (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)
Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SILICA-CRYSTALLINE (14464-46-1)

Listed on IARC (International Agency for Research on Cancer)
Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CIGR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

METHYL ETHYL KETOXIME (96-29-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CIGR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

TITANIUM DIOXIDE (13463-67-7)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
|---|---|---|---|-----------------------------------|
| Yes | No | No | No | |

ETHYLBENZENE (100-41-4)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
|---|---|---|---|-----------------------------------|
| Yes | No | No | No | 54 µg/day |

TITANIUM DIOXIDE (13463-67-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

ETHYLBENZENE (100-41-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

QUARTZ (14808-60-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SILICA-CRYSTALLINE (14464-46-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

RURAL MANOR II SOLID COLOR EXTERIOR STAIN - DEEPTONE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

| | |
|------|---|
| H225 | Highly flammable liquid and vapor |
| H226 | Flammable liquid and vapor |
| H227 | Combustible liquid |
| H302 | Harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H332 | Harmful if inhaled |
| H340 | May cause genetic defects |
| H350 | May cause cancer |
| H351 | Suspected of causing cancer |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H401 | Toxic to aquatic life |

SDS US (GHS HazCom 2012)

RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.