



RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 11/18/2016 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL
Product code : 714104

1.2. Relevant identified uses of the substance or mixture and uses advised against

Restrictions on use : Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Rodda Paint Co.
6107 North Marine Drive
Portland, Oregon 97203 - US
T (503) 521-4300
www.rodmapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3	H226
Skin sensitization Category 1	H317
Germ cell mutagenicity Category 1B	H340
Carcinogenicity Category 1B	H350
Hazardous to the aquatic environment - Acute Hazard Category 2	H401
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

GHS09

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
H317 - May cause an allergic skin reaction
H340 - May cause genetic defects
H350 - May cause cancer
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from sparks, open flames, hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing vapors, mist, fume
P272 - Contaminated work clothing must not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear protective gloves, eye protection
P302+P352 - If on skin: Wash with plenty of soap & water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see Seek medical attention if irritation develops. on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use ABC-powder, carbon dioxide (CO₂), foam, Water fog. to extinguish
P391 - Collect spillage
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
MINERAL SPIRITS	(CAS No) 64741-65-7	53.5	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
DIPENTENE #122	(CAS No) 138-86-3	5.4	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	(CAS No) 64742-48-9	1	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
ETHYLENE GLYCOL	(CAS No) 107-21-1	1	Acute Tox. 4 (Oral), H302
METHYL ETHYL KETOXIME	(CAS No) 96-29-7	0.5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
ETHYLBENZENE	(CAS No) 100-41-4	0.1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Reactivity : Flammable liquid and vapor.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing vapors, mist, fume.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing vapors, mist, fume.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ETHYLENE GLYCOL (107-21-1)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³ (aerosol only)
ACGIH	Remark (ACGIH)	URT & eye irr

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHYL ETHYL KETOXIME (96-29-7)		
AIHA	WEEL TWA (ppm)	10 ppm
DIPENTENE #122 (138-86-3)		
Not applicable		
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Not applicable		
ETHYLBENZENE (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
MINERAL SPIRITS (64741-65-7)		
Not applicable		

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Personal protective equipment : Dust/aerosol mask. Gloves. Insufficient ventilation: wear respiratory protection. Protective goggles.



Hand protection : Protective gloves.
Eye protection : Safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Wear respiratory protection.
Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear to cloudy.
Color : amber
Odor : kerosene-like
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : ≥ 57 °C
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Not applicable.
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Specific gravity : 0.85

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific gravity / density	: 7.12 lb/gal
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 300 mm ² /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ETHYLENE GLYCOL (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rat	10600 mg/kg
ATE US (oral)	500.000 mg/kg body weight
ATE US (dermal)	10600.000 mg/kg body weight
METHYL ETHYL KETOXIME (96-29-7)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	1000 - 1800 mg/kg
ATE US (oral)	930.000 mg/kg body weight
ATE US (dermal)	1000.000 mg/kg body weight
DIPENTENE #122 (138-86-3)	
LD50 oral rat	5300 mg/kg
ATE US (oral)	5300.000 mg/kg body weight
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
ETHYLBENZENE (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.4 mg/l/4h
ATE US (oral)	3500.000 mg/kg body weight

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLBENZENE (100-41-4)	
ATE US (dermal)	15400.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	17.400 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

MINERAL SPIRITS (64741-65-7)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

ETHYLBENZENE (100-41-4)	
IARC group	2B - Possibly Carcinogenic to Humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
--------------------------------------	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects. Toxic to aquatic life.
-------------------	---

ETHYLENE GLYCOL (107-21-1)	
LC50 fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

METHYL ETHYL KETOXIME (96-29-7)	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

ETHYLBENZENE (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

MINERAL SPIRITS (64741-65-7)	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)

12.2. Persistence and degradability

No additional information available

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

ETHYLENE GLYCOL (107-21-1)	
Log Pow	-1.93
METHYL ETHYL KETOXIME (96-29-7)	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)
ETHYLBENZENE (100-41-4)	
BCF fish 1	15
Log Pow	3.2

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 3 - Flammable liquid



Dangerous for the environment : Yes
Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672) T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

TDG

Transport by sea

UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

Air transport

UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ETHYLENE GLYCOL	CAS No 107-21-1	1%
ETHYLBENZENE	CAS No 100-41-4	0.1%

ETHYLENE GLYCOL (107-21-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ 5000 lb

SARA Section 313 - Emission Reporting 1.0 %

METHYL ETHYL KETOXIME (96-29-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DIPENTENE #122 (138-86-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
ETHYLBENZENE (100-41-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
MINERAL SPIRITS (64741-65-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

ETHYLENE GLYCOL (107-21-1)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
METHYL ETHYL KETOXIME (96-29-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
DIPENTENE #122 (138-86-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 3 - Combustible Liquid
ETHYLBENZENE (100-41-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
MINERAL SPIRITS (64741-65-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory	

EU-Regulations

ETHYLENE GLYCOL (107-21-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
METHYL ETHYL KETOXIME (96-29-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
DIPENTENE #122 (138-86-3)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
ETHYLBENZENE (100-41-4)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
MINERAL SPIRITS (64741-65-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	

National regulations

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLENE GLYCOL (107-21-1)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

METHYL ETHYL KETOXIME (96-29-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

DIPENTENE #122 (138-86-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

ETHYLBENZENE (100-41-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

MINERAL SPIRITS (64741-65-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLENE GLYCOL (107-21-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	

ETHYLBENZENE (100-41-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	54 µg/day

ETHYLENE GLYCOL (107-21-1)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

DIPENTENE #122 (138-86-3)
U.S. - New Jersey - Right to Know Hazardous Substance List

ETHYLBENZENE (100-41-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

HMIS III Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur * - Chronic (long-term) health effects may result from repeated overexposure
Flammability	: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
Physical	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.
Personal protection	: G G - Safety glasses, Gloves, Vapor respirator

RURAL MANOR SEMI TRANSPARENT STAIN NEUTRAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.