

MATERIAL SAFETY DATA SHEET

MSDS Name: RODDA PAINT WALL PRO Perm Prime 1.0 Vapor Primer

MSDS Number: 4034C Series (PF4506-01)

Version Number 0009

MSDS Date: 12/02/09

Page Number: 1 of 5

SECTION I - PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: RODDA PAINT PERM PRIME 1.0 VAPOR PRIMER (4034C Series)

CAS NUMBER: MIXTURE

HAZARD RATING: Health: 1 Fire: 1 Reactivity: 0 PPI: E

EPA REGISTRATION: NA

COMPANY IDENTIFICATION: Primer Specialties Inc.

PO BOX 821333; Vancouver, WA 98682

Contact: CUSTOMER SERVICE

Telephone/Fax: (360) 326-3999 / (360) 518-3716

PREPARER: Chris Pendergraft

EMERGENCY PHONE (24 HOUR): INFOTRAC (800) 535-5053

PRODUCT CLASS: WATERBASE PAINT

TRADE NAME: RODDA PAINT PERM PRIME 1.0 VAPOR PRIMER (4034C Series)

PRODUCT CODE: PFX03H39C

SECTION II - INGREDIENT AND HAZARD INFORMATION

HAZARDOUS INGREDIENTS - CAS NUMBER % TSCA HEALTH FIRE REACT PP:

No hazardous ingredients known at this time.

SECTION III - HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Ingestion and/or inhalation.

CARCINOGENICITY: This product does not contain any substance(s) listed as a carcinogen by NTP, IARC, or OSHA.

ACUTE (SHORT TERM) FOR PRODUCT:

EYES: Causes irritation.

SKIN: May cause skin irritation upon prolonged or repeated contact.

BREATHING: Causes slight irritation to nose and throat.

SWALLOWING: Ingestion may cause nausea, vomiting, diarrhea.

CHRONIC (LONG TERM) FOR PRODUCT OR COMPONENTS: Prolonged or repeated breathing of sprays, mists, or dusts in excess of the suggested TLV may cause nasal and respiratory irritations.

PERMISSIBLE EXPOSURE LEVEL FOR PRODUCT: No Threshold Limit Value (TLV) has been established for the product. Current Adopted Values listed by ACGIH suggests a TLV of 10 mg/m³ as Inhalable Particulates Not Otherwise Classified for sprays, mists or dust particulates generated during application or handling exposures.

MATERIAL SAFETY DATA SHEET

MSDS Name: RODDA PAINT WALL PRO Perm Prime 1.0 Vapor Primer

MSDS Number: 4034C Series (PF4506-01)

Version Number 0009

MSDS Date: 12/02/09

Page Number: 2 of 5

SECTION IV - FIRST AID MEASURES

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation continues, see a physician.

IF ON SKIN: Flush skin with water.

IF SWALLOWED: Induce vomiting. Call a physician immediately. Give large amounts of water or milk. Never give anything by mouth to an unconscious or convulsing person.

IF BREATHED: Remove person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

SECTION V - FIRE-FIGHTING MEASURES

FLAMMABILITY CLASS: IIIB

FLASH RANGE: >200F

EXPLOSIVE RANGE: Not Applicable

EXTINGUISHING MEDIA: Product is non-combustible.

SPECIAL FIREFIGHTING PROCEDURES: Use self-contained breathing apparatus with full face piece.

UNUSUAL FIRE & EXPLOSION HAZARDS: None.

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SMALL SPILLS: Contain spill immediately. Use inert material to absorb spilled material. Place absorbed spill into secure container for removal.

LARGE SPILLS: Use caution; spilled material may be extremely slippery. Contain spill immediately and prevent from entering the sewer system. Use an inert material to absorb spilled product.

NOTE: Rinsing this material down a sanitary sewer system can cause negative impact on monitoring systems. Contact local sewer authorities before attempting any discharges.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

PROTECT FROM FREEZING.

Store product between 40F- 120F. Frozen product may be irreversibly damaged. Product should be kept out of direct sunlight at all times. Keep container closed when not using.

MATERIAL SAFETY DATA SHEET

MSDS Name: RODDA PAINT WALL PRO Perm Prime 1.0 Vapor Primer

MSDS Number: 4034C Series (PF4506-01)

Version Number 0009

MSDS Date: 12/02/09

Page Number: 3 of 5

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS: ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

RESPIRATORY PROTECTION: Use an approved MSHA or NIOSH respirator for nuisance mists, dusts, or sprays.

VENTILATION: Use adequate ventilation to keep airborne concentrations below the exposure standard listed in Section II and/or Section V.

PROTECTIVE GLOVES: None normally required. Use is advisable.

EYE PROTECTION: Wear approved splash-proof chemical goggles. In a controlled environment where eye contact is minimal, Safety glasses with side shields may be sufficient protection.

OTHER PROTECTIVE EQUIPMENT: Avoid contact with clothing, dried product may be irremovable.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

FORM: LIQUID

APPEARANCE/COLOR: WHITE

ODOR: MILD

SOLUBILITY (IN WATER): DISPERSIBLE

pH VALUE: 9.0-9.5

BOILING RANGE: (WATER) 212F (100C)

PERM PRESSURE (mmHg): (WATER) 17 @ 68F (20C)

MELTING POINT: Not Available

EPERMATION RATE: Unavailable

PERM DENSITY: Non Volatile

PARTITION COEFFICIENT: Not Available

% VOLATILE VOLUME: INCLUDING WATER 72.88%

SPECIFIC GRAVITY: 1.19226

VOC: SEE SECTION XVI

MOLECULAR WEIGHT: MIXTURE

SECTION X - STABILITY AND REACTIVITY

STABILITY: This product is stable

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur

INCOMPATABILITY: None

CONDITIONS TO AVOID: Acids, strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide.

MATERIAL SAFETY DATA SHEET

MSDS Name: RODDA PAINT WALL PRO Perm Prime 1.0 Vapor Primer

MSDS Number: 4034C Series (PF4506-01)

Version Number 0009

MSDS Date: 12/02/09

Page Number: 4 of 5

SECTION XI - TOXICOLOGICAL INFORMATION

LETHAL DOSE INFORMATION (PPM):

ADDITIONAL TOXICOLOGICAL DATA FOR PRODUCT AND/OR INGREDIENTS: None known for product.

SECTION XII - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION FOR PRODUCT AND/OR INGREDIENTS: Aquatic toxicity not available.

SECTION XIII - DISPOSAL CONSIDERATIONS

EPA HAZARDOUS WASTE NUMBER: NONE

WASTE DISPOSAL METHOD: Product must be disposed of properly under Federal/State regulations for industrial waste. Disposal to a landfill may be permitted pending compliance with 40 CFR 264.314 & 265.314. This product when spilled or disposed of is a non-hazardous waste as defined in RCRA regulations (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

UN NUMBER: NONE

UN PACK GROUP: NA

UN CLASS: NA

ICAO/IATA CLASS: NONE

DOT HAZARD CLASS: NOT HAZARDOUS

CANADIAN TDG/WHMIS INFORMATION:

PIN NUMBER: None

TDG: NA

TDG ACT CLASS: NA

WHMIS: D2B

OTHER NAMES: None

SECTION XV - REGULATORY INFORMATION

EEC CLASSIFICATION: Irritant

This product is not a listed hazardous substance.

SECTION XVI - OTHER INFORMATION

ADDITIONAL PRECAUTIONS AND NOTES: Do not dilute or mix with other materials unless advised by supplier.

VOC INFORMATION: A Certified Product Data Sheet (CPDS) as outlined under Title 40 Part 63, Subpart JJ, Section 63.801 Definitions, detailing VOC content, will be available upon request from Direct Paint Manufacturing Inc.