

# WESTERINE

# EXTERIOR WOOD STAIN COLOR CARD

DECK - SIDING - FENCE

100% ACRYLIC WATER-BASED SOLID HIDE & SEMI-TRANSPARENT STAINS





## **Premium 100% Acrylic Stains for Decks, Siding and Fences**

The Very BEST! Designed Specifically to Withstand Wide-Ranging Weather & Environmental Conditions.

100% Acrylic, Waterborne STAIN developed with the Industry's latest Acrylic technology and with additional mold & mildew inhibitors. Designed to provide Superior resistance to cracking, peeling, and blistering. Formulated with less Volatile solvents to provide a long lasting decorative finish with a high degree of water-repellency when dry.

Homeowners and Professionals alike can rest assured that Decks, Siding, Trim, Doors and Fences will remain protected and beautified with the Cloverdale WeatherOne® Stains!

- PREMIUM OUALITY
- 100% ACRYLIC
- EXCELLENT COVERAGE
- SUPERIOR ADHESION
- MOISTURE REPELLENT
- RESISTS CRACKING, PEELING & BLISTERING
- RESISTANT TO MOLD & MILDEW ON FINISH
- PROTECTS AGAINST THE SUN'S UV RAYS
- HIGHLIGHTS/ENHANCES
  NATURAL TEXTURE OF WOOD

### **COLOR SELECTION TIPS**

- · Look to Gardens, Furniture or other Structural elements, such as Paving or Accent Stonework that will remain once the staining project is complete.
- · Consider neighboring Houses/Structures... You may find great inspiration from newly built homes or even other buildings in the neighborhood to create a color scheme.
- Lighter colors, such as Off-whites, tend to visually 'highlight' the surface being painted...If the goal is to draw the eye away from details, they should be painted the dominant color so as not to be noticeable.
- · Lighting impacts how colors are perceived...Make sure to **select** colors **outside**, in the area where they will be applied and **during** the hours, when they will be most enjoyed.

### **APPLICATION TIPS**

- · Chemically-treated wood **needs** to age at least 28 days and other new dimensional lumber **should** age 2–4 weeks before applying.
- **Watch out for weather!** DO NOT apply Stain in direct sunlight or within 6 hours before or after a rainfall.
- · Surface temperature of the wood **should** be below 95F.
- · Application conditions should ideally be between 50F-85F.
- For **optimal** protection of the wood, stain **all** 6 sides of the wood to seal and protect it from moisture before construction, **especially** for decks that are close to the ground with little air circulation under the deck boards.
- To <u>dispose</u> of any excess Stain remaining after the project is complete, **contact** your local municipality or your local Rodda Paint Store to understand the Stain recycling options available in your area.
- For complete application instructions, please refer to Technical Data Sheet (TDS) documents available online at www.roddapaint.com or contact your local Rodda Paint Representative.



## **Quality, Trust, Tradition Since 1932**

 Ask your Rodda Paint representative about the Cascadia Color Collection, a nature inspired color palette.

