

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : RESIST-X MATTE/GL1 DEEP
 Product code : 412703

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Rodda Paint Co.
 6107 N. Marine Dr.
 Portland, OR 97203 - US
 T (503) 521-4300
www.rodmapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Carcinogenicity Category	H350	May cause cancer
1B		
Hazardous to the aquatic environment - Acute Hazard Category 3	H402	Harmful to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H350 - May cause cancer
 H402 - Harmful to aquatic life

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P273 - Avoid release to the environment.
 P280 - Wear eye protection, face protection, protective gloves, protective clothing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P405 - Store locked up.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

RESIST-X MATTE/GL1 DEEP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
TITANIUM DIOXIDE	(CAS-No.) 13463-67-7	6.9	Carc. 2, H351
ALIPHATIC PETROLEUM DISTILLATES	(CAS-No.) 64741-88-4	0.2	Carc. 1B, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

RESIST-X MATTE/GL1 DEEP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

Not applicable

TITANIUM DIOXIDE (13463-67-7)

ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust)
IDLH	US IDLH (mg/m ³)	5000 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: white
Odor	: mild
Odor threshold	: No data available
pH	: 8.5 - 9.5
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available

RESIST-X MATTE/GL1 DEEP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapor density at 20 °C	: No data available
Specific gravity	: No data available
Specific gravity / density	: 9.88 lb/gal
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5530 mg/m ³ (Exposure time: 4 h)

TITANIUM DIOXIDE (13463-67-7)

LD50 oral rat	> 10000 mg/kg
Skin corrosion/irritation	: Not classified pH: 8.5 - 9.5
Serious eye damage/irritation	: Not classified pH: 8.5 - 9.5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

TITANIUM DIOXIDE (13463-67-7)

IARC group	2B - Possibly Carcinogenic to Humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

RESIST-X MATTE/GL1 DEEP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
-------------	--

EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
----------------	--

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose of contents/container to hazardous or special waste collection point in accordance with state and local regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

TITANIUM DIOXIDE (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RESIST-X MATTE/GL1 DEEP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

TITANIUM DIOXIDE (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

TITANIUM DIOXIDE (13463-67-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

National regulations

ALIPHATIC PETROLEUM DISTILLATES (64741-88-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations



WARNING

This product can expose you to TITANIUM DIOXIDE, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

TITANIUM DIOXIDE (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

TITANIUM DIOXIDE (13463-67-7)

U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 09/20/2024

Full text of H-phrases:

H350	May cause cancer
H351	Suspected of causing cancer
H402	Harmful to aquatic life

RESIST-X MATTE/GL1 DEEP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rodda Paint Co. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which Rodda Paint Co. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.